

DATASHEET

CIS-DS-011

REV A

20-10-2020

Fibre Management System (FMS)









CISFIBER Infra Solution's Fiber Management system (FMS) is a multi-purpose mechanical rackmount used to protect and store optical fibre patching with the provision of patch cord management. FMS features a slide out design for effective installation and maintenance. It provides a total solution for managing fiber optic cable. It's an innovative product build based on the inputs taken from real-time installers and site conditions. It's available in sizes 1U to 4U in a rack-mount category.

FEATURES / BENIFITS

- **19" Size**: Suitable for any 19" electronic equipment rack and extension mounting bracket could be used (option of 21" also available).
- Maximum capacity of 48F in SCPC/SCAPC in 1U.
- **Big trays** with maximum capacity of 24F splicing with proper bend radius and fiber storage. No need to measure fiber length before splicing.
- Rodent-proof design.
- Patch panel with 4 nos 6F **patch-plate design** (plate installation at back of panel for better ergonomics).
- Tube storage area provided separately so that loose tubes and pigtails don't interfere with each other
- Matt finish
- Magnetic locking top cover for ease of operation

APPLICATIONS

- Data Center, GMSC, MSC...
- Wide Area Network, POP Locations
- CATV
- Passive Optical Network
- Local Area Network
- FTTx applications



DATASHEET

CIS-DS-011 REV A

20-10-2020

SPECIFICATIONS

D		Values						
Parameters	Values							
	1U	2U	4U					
Dimension (H x W x D)	1U x 444 x 280	2U x 444 x 280	4U x 444 x 280					
Material	CRCA (MS) thickness 1.0mm and Powder Coa							
Adaptor Types	Max Capacity (Fibers)							
sc	48	96	96					
FC	24	48	96					
LC	48	96	192					
	General Specifications							
No of cables Entries/Exit	2	4	4					
Access	Front with Telescopic slides	Front with Telescopic slides	Front with Telescopic slides					
Cable Entry	From Rear	From Rear	From Rear					
Loose Tube Storage Space	Separate Space Available	Separate Space Separate Space Available Available						
Cable Diameter	5 to 18 mm	12 to 18 mm	12 to 18 mm					
Pigtail Length	1.5 mtr	1.5 mtr	1.5 mtr					
No. of Splice Trays	Splice Trays 2 4		8					
Splice / Tray	24	24	24					



DATASHEET

CIS-DS-011 REV A 20-10-2020

ORDERING GUIDE

TENAC		
1 FIVIS		

Product Family		Interface Type			Loading		
Type	Catalogue Code	LIU Size	Туре	Catalogue Code	Capacity	Туре	Catalogue Code
Telecommunications FMS			/		,	Fully Loaded with Adaptors and	
Sliding	TFMS	1U	SC/PC	SCP	OF*	Pigtails	FL
		2U	SC/ APC*	SCA	6F*	Loaded with Adaptors	AL
		4U	LC/PC	LCP	12F*	Unloaded	UL
			LC/ APC*	LCA	24F*		
			FC/PC	FCP	48F**		
			FC/ APC*	FCA	96F***		
			ST/PC	STP	192F****		
			*APC version only available with SM Fibre only		*0F/6F/12F/24F 1U FMS **48F 1U LC		
					Duplex		
					**48F 2U SC/FC/ ST Simplex		
					***9fF 2U LC Duplex		
					***96F 4U SC/ FC/ST Simplex		
					****192F 4U LC Duplex		

*Note: For Multi-mode FMS, fibre type to be put at last.

For Eg: TFMS-1U-LCP-24F-FL-OM4 for FMS with OM4 pigtails and adaptors