



Optical Termination Box (OTB-B)



CISFIBER Infra Solution's Optical Termination Box (OTB) is FTTx box which is used to patch up to 24 fibers and splice up to 32 fibers. It can handle SCPC/SCAPC/LCPC/LCAPC/FCPC/FCAPC adaptors and connectors. This is a ruggedized termination box with IP65 compliant rating.

FEATURES / BENEFITS

- IP65 Rating Compliant
- 32F Splicing capacity, 24F Patching Capacity
- Separate storage of 900micron input pigtailed and output drop cables up to 1.5m, loose tube, with Proper Bend Control
- One midspan, 1 Distribution Port Option
- Separate 8 drop cable/fiber patch cord exit with size big enough for passing connectorized drop cable
- Complies to ISO/IEC, ASTM-D, GR 487 Standards



DATASHEET

CIS-DS-026

REV B

22-02-2021

APPLICATION

- ◆ FTTX
- ◆ Outdoor Pole/Wall Mount
- ◆ Telecommunications

SPECIFICATIONS

Product Information	
Item	Parameter
Size, MM	280 x 225 x 106
Material	ABS
IP	65
Available adapter	SC/PC, SC/APC, LC/PC, LC/APC, FC/PC, FC/APC

Ordering Guide

XXX - X	XXF	XXX	XX
OTB Type B – OTB-B	Capacity 16F to 24F	Connector Type: SC/PC - SCP, SC/APC - SCA, LC/PC – LCP, LC/APC—LCA, FC/PC—FCP, FC/APC—FCA	UL – Unloaded FL – Fully Loaded